



WHEEL-CHECK®

THE LOOSE WHEEL-NUT INDICATOR

For accuracy, please check nut size with a socket wrench



WHEEL-CHECK PART # HIGH VISIBILITY GREEN	WHEEL-TORQUE PART # RED	HIGH TEMPERATURE WHEEL-CHECK ORANGE (WITHSTAND UP TO 450° F)	NUT SIZES	
			INCHES	MM
WLCH-AA	WLTO-AA	WCHT-AA	1 1/2	38.1
WLCH-A	WLTO-A	WCHT-A	1 1/2	37.5
WLCH-B	WLTO-B	WCHT-B	1 5/16	33.0
WLCH-C	WLTO-C		7/8	22.0
WLCH-D	WLTO-D		1 1/16	27.0
WLCH-E	WLTO-E		13/16	20.5
WLCH-F	WLTO-F	WCHT-F	1 1/4	31.0
WLCH-G	WLTO-G		1	25.0
WLCH-H	WLTO-H	WCHT-H	1 9/16	40.5
WLCH-I	WLTO-I	WCHT-I	27/32	20.8
WLCH-J	WLTO-J	WCHT-J	1 3/4	44.0
WLCH-K	WLTO-K	WCHT-K	1 3/16	30.0
WLCH-L	WLTO-L	WCHT-L	1 9/32	32.0
WLCH-M	WLTO-M		15/16	23.8
WLCH-N	WLTO-N		1 1/8	28.0
WLCH-O	WLTO-O		3/4	19.0
WLCH-P	WLTO-P		1 3/8	35.0

HIGH TEMPERATURE WHEEL-CHECKS CAN WITHSTAND TEMPERATURES UP TO 450° F.

Mainly used in the transit and some waste disposal industries.

*High temperature Wheel-Checks will not detect any break or bearing problems.

CUSTOM SIZES AND COLOURS ARE AVAILABLE UPON REQUEST.

The use of Wheel-Check® in no way guarantees wheel-offs will not occur.

T: 888.829.1556/905.829.0909 • F: 905.829.0808 • E: info@wheel-check.com • www.wheel-check.com

© Wheel-Check® is a registered trademark and division of Wheel-Safety®. The Home of Wheel-Checks.